

## NORMAC BR-3TM TROWELABLE URETHANE

### PRODUCT:

BR-3TM is a 100% solids, trowelable putty grade polyurethane material that when mixed in proper portions, will yield a tough rubbery compound with exceptional abrasion and tear resistance

### DESCRIPTION:

Typical uses for BR-3TM are conveyor parts, belt repair and as a trowelable lining. BR-3TM comes in convenient pre-weighed containers, that when mixed properly, can be applied in any thickness without shrinkage, due to the absence of volatile solvents. The cured repair can be machined or buffed to a smooth finish.



### PROPERTIES:

Shelf Life	2 years +
Hardness	75 +/-5 Shore A
Tear Strength	45 pli
Flash Point	-4°C to -20°C (24.8°F to -4°F)
Application Life	10 – 15 minutes @ 21°C
Ratio	Part A: > 204 °C    Part B: 262 °C
Shipping	DGR – Dangerous Goods

Rev.3

Product Code	Kit Size	Package Size Details	
		Part A	Part B
3TM-1	250g	178g – 250ml / ½ pint can	72g – 60ml / 2 ounce bottle
3TM-2	500g	347g – 500ml / pint can	143g – 125ml / 4 ounce bottle
3TM-3	1kg	714g – 1L / quart can	286g – 250ml / 8 ounce bottle
3TM-4	5kg	3,572g – 4L / gallon can	1,428g – ½ gallon bottle

This data is based on information believed to be reliable and is offered solely for evaluation. Normac products are sold with the understanding that clients make their own tests to determine the suitability of these products for their particular application. Since the use of this product is beyond the control of the Seller, the Buyer assumes all risks of use or handling, whether in accordance with directions or not, as the Seller makes no warranty, expressed or implied, concerning this product.